

# COMPOSITION 6 ELEMENTS ASMARA

## Designer

Bernard Govin



## Technical characteristics

**CONSTRUCTION** : an all-foam model.

Base in polyether foam (elements 501 and 503: 34 kg/m<sup>3</sup> - 5.7 kPa ; elements 502 and 504 : 28 kg/m<sup>3</sup> - 4.8 kPa).

**COMFORT** : elements 501 and 504 are composed of high resilience polyurethane Bultex foam (38 kg/m<sup>3</sup> - 2.8 kPa and 36 kg/m<sup>3</sup> - 2.8 kPa) clad in 110 g/m<sup>2</sup> polyester quilting.

Element 502 is composed of high resilience polyurethane Bultex foam (36 kg/m<sup>3</sup> - 2.8 kPa and 38 kg/m<sup>3</sup> - 2.8 kPa) clad in 110 g/m<sup>2</sup> polyester quilting.

Element 503 is composed of high resilience polyurethane Bultex foam (38 kg/m<sup>3</sup> - 3.6 kPa) clad in 110 g/m<sup>2</sup> polyester quilting. Cushion in ultra-flexible foam (50 kg/m<sup>3</sup> - 1.8 kPa).

**MAKING-UP** : fabrics with elastic

## Dimensions

Height 490 mm | Width 1,560 mm | Depth 1,530 mm |  
Seat height 210 mm

More information on  
[www.ligne-roset.com](http://www.ligne-roset.com)

**ligne roset**<sup>®</sup>  
depuis 1860

© Ligne Roset 2025

properties must be selected. 5 mm  
baguette stitch detailing on all elements.  
Twin-needle stitching on cushion. Covers  
may be removed by a professional.