

# COMPOSITION ASMARA

## Designer

Bernard Govin



## Dimensions

## Technical specifications

CONSTRUCTION : an all-foam model. Base in polyether foam (elements 501 and 503: 34 kg/m<sup>3</sup> – 5.7 kPa ; elements 502 and 504 : 28 kg/m<sup>3</sup> – 4.8 kPa).

COMFORT : elements 501 and 504 are composed of high resilience polyurethane Bultex foam (38 kg/m<sup>3</sup> – 2.8 kPa and 36 kg/m<sup>3</sup> – 2.8 kPa) clad in 110 g/m<sup>2</sup> polyester quilting.

Element 502 is composed of high resilience polyurethane Bultex foam (36 kg/m<sup>3</sup> – 2.8 kPa and 38 kg/m<sup>3</sup> – 2.8 kPa) clad in 110 g/m<sup>2</sup> polyester quilting.

Element 503 is composed of high resilience polyurethane Bultex foam (38 kg/m<sup>3</sup> – 3.6 kPa) clad in 110 g/m<sup>2</sup> polyester quilting. Cushion in ultra-flexible foam (50 kg/m<sup>3</sup> – 1.8 kPa).

MAKING-UP : fabrics with elastic properties must be selected. 5 mm baguette stitch detailing on all elements. Twin-needle stitching on cushion. Covers may be removed by a professional.